

View Online at https://aerobasegroup.com/nsn/5910-00-808-4343

#### **Body Style:**

W/o mtg facilities, radial terminalsw/o mtg facilities, radial terminalsw/o mtg facilities, radial terminals

## **Reliability Indicator:**

Not establishednot establishednot established

### **Body Diameter:**

0.225 inches

#### **Body Length:**

0.430 inches

#### **Terminal Height From Body:**

1.312 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### Insulation Resistance At Maximum Operating Temp:

1000.0 megohms

#### **Capacitance Value Per Section:**

20.000 picofarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

## Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-150.0 single section

#### Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

### Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-60.0/+60.0 single section

#### **Tolerance Range Per Section:**

-2.00/+2.00 percent single section

#### **Case Material:**

Ceramic

Insulation Resistance At Reference Temp:

50000.0 megohms

# Quality Factor At Reference Temp:

800.000

# **Terminal Surface Treatment:**

Solder

# Test Data Document:

81349-mil-c-20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 uninsulated wire lead

### Shelf Life:

N/a

Unit Of Measure:



Demilitarization:

No

Fiig:

A010b0