NSN 5910-00-808-5844



Electrolytic Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-00-808-5844 **Body Style:** W/o mtg facilities, axial terminals Reliability Indicator: Not established **Terminal Length:** 1.500 inches **Body Diameter:** 0.135 inches **Body Length:** 0.286 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Anode Type:** Solid **Electrical Polarization:** Polarized **Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 0.100 microfarads single section **Nonderated Operating Temp:** Between -80.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 8.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section **Case Material:** Metal **Capacitive Electrode Material: Dissipation Factor At Reference Tempurature In Percent:** 2.0000 Dc Leakage At Reference Temp: 0.600 microamperes **Terminal Surface Treatment:** Solder **Case Insulation Material: Plastic**

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-00-808-5844

Electrolytic Fixed Capacitor - Page 2 of 2



| | | fe: |
|--|--|-----|
| | | |
| | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0