## NSN 5910-00-810-4277

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-810-4277 **Body Style:** W/o mtg facilities, axial terminals Reliability Indicator: Not established **Terminal Length:** 0.062 inches **Body Diameter:** 1.125 inches **Body Length:** 2.031 inches **Terminal Diameter:** 0.094 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Solid **Impedance At Minimum Operating Tempurature In Ohms:** 200.0 **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 25.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 390.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 450.0 dc single section **Tolerance Range Per Section:** -15.00/+75.00 percent single section Case Material: Metal **Capacitive Electrode Material: Tantalum Equivalent Series Resistance At Reference Tempurature In Ohms:** 12.50 Dc Leakage At Reference Temp: 39.000 microamperes **Terminal Surface Treatment:** Solder

**Case Insulation Material:** 

**Plastic** 

## NSN 5910-00-810-4277

Electrolytic Fixed Capacitor - Page 2 of 2



ī	ermina	ı	Type	Δnd	Qua	antity.
ı	CHILLING	41	INDE	Allu	wu	aiititv.

1 solder stud and 1 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0