

View Online at <https://aerobasegroup.com/nsn/5910-00-811-2364>

Body Style:

W/o mtg facilities, radial terminals/w/o mtg facilities, radial terminals

Reliability Indicator:

Not established/not established

Terminal Length:

1.500 inches / 1.500 inches

Body Diameter:

0.290 inches

Body Length:

0.235 inches

Center To Center Distance Between Terminals Parallel To Diameter:

0.250 inches

Terminal Diameter:

0.025 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

End Application:

Ticonderoga class cg (47); forrestal class cv; iwo jima class lph; aircraft, tomcat f-14; wasp class lhd; ship, ohio class ssn (trident); aircraft, prowler ea-6b

Capacitance Value Per Section:

1.000 picofarads single section

Nonderated Operating Temp:

Between 0.0 degrees celsius and 65.0 degrees celsius

Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

1000.0 dc single section

Tolerance Of Temperature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-0.20/+0.20 picofarads single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

7500.0 megohms

Quality Factor At Reference Temp:

400.0000

Terminal Surface Treatment:

Solder

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0