NSN 5910-00-812-4052

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-812-4052
Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Not established
Terminal Length:
Between 1.625 inches and 2.625 inches
Body Diameter:
Between 0.384 inches and 0.416 inches
Body Length:
Between 0.938 inches and 1.000 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
1.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Detricent colo degrees colorde and colo degrees colorde
Nonderated Continuous Voltage Rating And Type Per Section:
Nonderated Continuous Voltage Rating And Type Per Section:
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section:
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material:
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Metal
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp:
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 6000.0 megohm-microfarads
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 6000.0 megohm-microfarads Terminal Surface Treatment:
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 6000.0 megohm-microfarads Terminal Surface Treatment: Solder
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 6000.0 megohm-microfarads Terminal Surface Treatment: Solder Case Insulation Material:
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 6000.0 megohm-microfarads Terminal Surface Treatment: Solder Case Insulation Material: Plastic
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 6000.0 megohm-microfarads Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity:
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 6000.0 megohm-microfarads Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 6000.0 megohm-microfarads Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life:
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 6000.0 megohm-microfarads Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 6000.0 megohm-microfarads Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a

Fiig:

A010b0