NSN 5910-00-814-0362

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-814-0362

Body Style:
W/mtg bracket, axial terminals
Reliability Indicator:
Not established
Terminal Length:
0.297 inches
Body Diameter:
0.750 inches
Body Length:
1.875 inches
Continuous Current Rating In Amps:
1.0
Unthreaded Mounting Hole Diameter:
0.156 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Mounting Facility Type And Quantity:
1 unthreaded mounting holes
Features Provided:
Hermetically sealed case
Insulation Resistance At Maximum Operating Temp:
600.0 megohms
Capacitance Value Per Section:
1.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
400.0 dc single section
Tolerance Range Per Section:
-5.00/+5.00 percent single section
Case Material:
Metal
Insulation Resistance At Reference Temp:
12000.0 megohms
Power Factor At Reference Tempurature In Percent:
1.0000
Terminal Surface Treatment:
Solder
Test Data Document:
08903-bacc11mpe105b drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer

drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

2 tab, solder lug

Terminal Type And Quantity:

NSN 5910-00-814-0362

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Sneit Lite:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A010b0