## NSN 5910-00-815-8933

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-815-8933 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.625 inches **Body Diameter:** 0.670 inches **Body Length:** 1.562 inches **Continuous Current Rating In Amps:** 1.0 **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Features Provided:** Hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 10.0 megohm-microfarads **Capacitance Value Per Section:** 2.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section Case Material: Metal **Insulation Resistance At Reference Temp:** 2000.0 megohm-microfarads **Power Factor At Reference Tempurature In Percent:** 1.0000 **Terminal Surface Treatment:** Solder **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5910-00-815-8933

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



| _ |    | •• | • - |     |             |     |    |
|---|----|----|-----|-----|-------------|-----|----|
| 1 | em |    | ゖっ  | riz | <b>2</b> †1 | n   |    |
| _ |    |    | ıιa | 114 | au          | VII | ١. |

No

Fiig:

A010b0