Glass Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-816-3998

Body Style:

W/o mtg facilities, terminals on opposite surfaces

Reliability Indicator:

Not established

Terminal Length:

1.125 inches

Body Length:

Between 0.297 inches and 0.391 inches

Body Width:

Between 0.047 inches and 0.109 inches

Body Height:

Between 0.141 inches and 0.203 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Features Provided:

Hermetically sealed case

Insulation Resistance At Maximum Operating Temp:

10000.0 megohms

Capacitance Value Per Section:

150.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

140.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-25.0 to 25.0 single section

Tolerance Range Per Section:

-5.00 to 5.00 percent single section

Case Material:

Glass

Insulation Resistance At Reference Temp:

100000.0 megohms

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

Glass Dielectric Fixed Capacitor - Page 2 of 2

Demilitarization:

No

Fiig:

A010b0

