Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-816-5675

## **Body Style:**

W/thd bushing mtg, terminal (s) on one end

**Reliability Indicator:** 

Not established

# **Terminal Length:**

1.000 inches

#### **Body Diameter:**

1.500 inches

#### **Body Length:**

4.500 inches

### Schematic Diagram Designator:

Electrod (s) grounded to case

### Mounting Facility Screw Thread Series Designator:

Unf

### Mounting Facility Type And Quantity:

1 threaded bushing

## Features Provided:

Mounting hardware and hermetically sealed case

# Insulation Resistance At Maximum Operating Temp:

15.0 megohm-microfarads

## Capacitance Value Per Section:

2.000 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

#### **Thread Size:**

0.750 inches

## Nonderated Continuous Voltage Rating And Type Per Section:

1000.0 dc single section

#### **Tolerance Range Per Section:**

-10.00 to 10.00 percent single section

#### **Case Material:**

Metal

# Insulation Resistance At Reference Temp:

1500.0 megohm-microfarads

# Dissipation Factor At Reference Tempurature In Percent:

1.0000

#### **Test Data Document:**

81349-mil-c-25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

1 threaded stud

Shelf Life:

N/a

Paper Dielectric Fixed Capacitor - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0