

View Online at https://aerobasegroup.com/nsn/5910-00-817-9404

Thread Class:
2a
Body Style:
Piston
Bushing Diameter: 0.250 inches
Bushing Length:
0.257 inches
Body Length:
Any acceptable
Overall Diameter:
0.310 inches
Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Quality Factor At 25 Deg Celsius:
500.0
Mounting Facility Screw Thread Series Designator:
Unf
Inclosure Type:
Encapsulated
Adjustment Device Torque:
Between 1.500 inch-ounces and 10.000 inch-ounces
Bushing Shape:
Round w/flat
Insulation Dc Resistance At 25 Deg Celsius:
1000.0 gigohms
Bushing Width:
Any acceptable
Mounting Facility Type And Quantity:
1 threaded bushing
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Thread Size:
0.250 inches
Capacitance Range In Picofarads:
+1.0/+14.0 single section
Nonderated Voltage Rating And Type:
1000.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 hex socket
Capacitance Drift In Picofarads:
0.04 single section



Terminal Type And Quantity:

1 wire lead and 1 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A096a0