## NSN 5910-00-818-2702

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-818-2702

| Body Style:  |
|--|
| W/o mtg facilities, radial terminalsw/o mtg facilities, radial terminalsw/o mtg facilities, radial terminals |
| Reliability Indicator:   |
| Not establishednot established   |
| Terminal Length:   |
| 1.500 inches   |
| Body Diameter:   |
| 0.385 inches   |
| Body Length:   |
| 0.187 inches   |
| Center To Center Distance Between Terminals Parallel To Diameter:  |
| 0.250 inches   |
| Terminal Diameter:   |
| 0.025 inches   |
| Schematic Diagram Designator:  |
| No common or grounded electrode (s)  |
| Capacitance Value Per Section:   |
| 10000.000 picofarads single section  |
| Voltage Tempurature Limits Per Section In Percent Capacitance Change:  |
| -56.0/+22.0 without voltage applied single section   |
| Nonderated Operating Temp:   |
| Between 10.0 degrees celsius and 85.0 degrees celsius  |
| Nonderated Continuous Voltage Rating And Type Per Section:   |
| 500.0 dc single section  |
| Tolerance Range Per Section:   |
| -20.00/+80.00 percent single section   |
| Case Material:   |
| Plastic  |
| Insulation Resistance At Reference Temp:   |
| 10000.0 megohms  |
| Power Factor At Reference Tempurature In Percent:  |
| 2.5000   |
| Terminal Surface Treatment:  |
| Solder   |
| Terminal Type And Quantity:  |
| 2 uninsulated wire lead  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
|  |

No

## NSN 5910-00-818-2702

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0