

View Online at <https://aerobasegroup.com/nsn/5910-00-819-2100>

**Body Style:**

W/mtg tabs/flanges, terminal (s) on one surface

**Reliability Indicator:**

Not established

**Body Length:**

2.000 inches

**Body Width:**

1.750 inches

**Body Height:**

0.875 inches

**Unthreaded Mounting Hole Diameter:**

0.188 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.375 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Mounting Facility Type And Quantity:**

2 unthreaded mounting holes

**Features Provided:**

Hermetically sealed case

**Insulation Resistance At Maximum Operating Temp:**

10.0 megohm-microfarads

**Capacitance Value Per Section:**

1.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

400.0 dc single section

**Tolerance Range Per Section:**

-10.00 to 10.00 percent single section

**Case Material:**

Metal

**Insulation Resistance At Reference Temp:**

6000.0 megohms

**Dissipation Factor At Reference Temperature In Percent:**

1.0000

**Terminal Surface Treatment:**

Solder

**Test Data Document:**

81349-mil-c-25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0