NSN 5910-00-821-8533

W/mtg tabs/flanges, terminal (s) on one surface

Body Style:

Shelf Life:

N/a

Reliability Indicator:

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-821-8533

| Not established |
|--|
| Terminal Length: |
| 0.312 inches |
| Body Length: |
| 1.125 inches |
| Body Width: |
| 0.687 inches |
| Body Height: |
| 1.000 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.141 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 1.438 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Mounting Facility Type And Quantity: |
| 2 unthreaded mounting holes |
| Features Provided: |
| Hermetically sealed case |
| Capacitance Value Per Section: |
| 0.500 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 400.0 dc single section |
| Tolerance Range Per Section: |
| -20.00 to 40.00 percent single section |
| Case Material: |
| Metal |
| Insulation Resistance At Reference Temp: |
| 3000.0 megohms |
| Dissipation Factor At Reference Tempurature In Percent: |
| 1.0000 |
| Terminal Surface Treatment: |
| Solder |
| Terminal Type And Quantity: |
| 2 tab. solder lug |

NSN 5910-00-821-8533

Paper Dielectric Fixed Capacitor - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A010b0