NSN 5910-00-822-5826

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-822-5826

Body Style:	
W/thd bushing mtg, terminals on opposite ends	
Reliability Indicator:	
Not established	
Terminal Length:	
0.296 inches	
Body Diameter:	
1.000 inches	
Body Length:	
1.874 inches	
Continuous Current Rating In Amps:	
1.0	
Schematic Diagram Designator:	
No common or grounded electrode (s)	
Mounting Facility Screw Thread Series Designator:	
Unf	
Mounting Facility Type And Quantity:	
1 threaded bushing	
Features Provided:	
Hermetically sealed case	
Insulation Resistance At Maximum Operating Temp:	
40.0 megohm-microfarads	
Capacitance Value Per Section:	
2.000 microfarads single section	
Nonderated Operating Temp:	
Between -55.0 degrees celsius and 125.0 degrees celsius	
Thread Size:	
0.312 inches	
Nonderated Continuous Voltage Rating And Type Per Section:	
400.0 dc single section	
Tolerance Range Per Section:	

-10.00/+10.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

2000.0 megohm-microfarads

Power Factor At Reference Tempurature In Percent:

1.0000

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 tab, solder lug

NSN 5910-00-822-5826

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A010b0