## NSN 5910-00-822-6844

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-822-6844 **Body Style:** W/thd bushing mtg, terminal (s) on one end Reliability Indicator: Not established **Body Diameter:** 0.750 inches **Body Length:** 1.812 inches **Schematic Diagram Designator:** Electrod (s) grounded to case **Mounting Facility Screw Thread Series Designator:** Unf **Mounting Facility Type And Quantity:** 1 threaded bushing **Features Provided:** Hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 40.0 megohm-microfarads **Capacitance Value Per Section:** 1.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius **Thread Size:** 0.312 inches Nonderated Continuous Voltage Rating And Type Per Section: 400.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:** 4000.0 megohm-microfarads **Dissipation Factor At Reference Tempurature In Percent:** 1.2500 **Power Factor At Reference Tempurature In Percent:** 1.0000 **Terminal Surface Treatment:** Solder

**Terminal Type And Quantity:** 

1 tab, solder lug

Shelf Life:

N/a

## NSN 5910-00-822-6844

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A010b0