

View Online at <https://aerobasegroup.com/nsn/5910-00-822-8688>

Body Style:

W/mtg tabs/flanges, terminal (s) on one surface

Reliability Indicator:

Not established

Mounting Slot Width:

Between 0.172 inches and 0.234 inches

Body Length:

Between 3.688 inches and 3.812 inches

Body Width:

Between 2.188 inches and 2.312 inches

Body Height:

Between 4.750 inches and 4.937 inches

Center To Center Distance Between Terminals Parallel To Length:

Between 1.844 inches and 1.906 inches

Terminal Height From Body:

2.125 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 4.469 inches and 4.531 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.219 inches and 1.281 inches

Mounting Facility Type And Quantity:

4 mounting slots

Features Provided:

Hermetically sealed case and mounting hardware

Insulation Resistance At Maximum Operating Temp:

1000.0 megohm-microfarads

Capacitance Value Per Section:

0.500 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

400.0 ac-peak single section and 10000.0 dc single section

Tolerance Of Temperature Coefficient Per Section In Ppm Per Deg Celsius:

-2.0/+2.0 single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

10000.0 megohm-microfarads

Power Factor At Reference Temperature In Percent:

0.500

Dielectric Material:

Plastic polyester

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0