## NSN 5910-00-822-8732

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-822-8732 **Body Style:** W/thd bushing mtg, terminals on opposite ends **Reliability Indicator:** Not established **Body Diameter:** 0.875 inches **Body Length:** 0.500 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Solid **Electrical Polarization:** Polarized **Mounting Facility Type And Quantity:** 1 threaded bushing **Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 75.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 175.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 30.0 dc single section **Tolerance Range Per Section:** -15.00/+75.00 percent single section **Case Material:** Metal **Capacitive Electrode Material: Tantalum Terminal Surface Treatment:** Solder **Test Data Document:** 18876-10044176 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 2 tab, solder lug Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 5910-00-822-8732

Electrolytic Fixed Capacitor - Page 2 of 2



Fiig:

A010b0