

NSN 5910-00-822-9405 Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2	AeroBa Gr
View Online at https://aerobasegroup.com/nsn/5910-00-822-9405	
Body Style:	
W/thd mtg studs, terminal (s) on the end	
Reliability Indicator:	
Not established	
Terminal Length:	
1.620 inches	
Body Diameter:	
0.416 inches	
Body Length:	

1.157 inches

Center To Center Distance Between Terminals Parallel To Diameter:

0.140 inches

Terminal Diameter:

0.032 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.800 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Mounting Facility Screw Thread Series Designator:

Unc

Mounting Facility Type And Quantity:

2 threaded mounting studs

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

0.220 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 100.0 degrees celsius

Thread Size:

0.112 inches

Nonderated Continuous Voltage Rating And Type Per Section:

400.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

250.0 megohm-microfarads

Dissipation Factor At Reference Tempurature In Percent:

1.000

Terminal Surface Treatment:

Solder

NSN 5910-00-822-9405

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Dielectric Material:
Paper
Case Insulation Material:
Plastic
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A010b0