

View Online at https://aerobasegroup.com/nsn/5910-00-822-9407

# Body Style:

W/thd mtg studs, terminal (s) on the end

## **Reliability Indicator:**

Not established

## Terminal Length:

Between 1.625 inches and 2.625 inches

#### **Body Diameter:**

0.416 inches

#### **Body Length:**

1.157 inches

#### Center To Center Distance Between Terminals Parallel To Diameter:

0.140 inches

## **Terminal Diameter:**

0.032 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.800 inches

## Schematic Diagram Designator:

No common or grounded electrode (s)

## Mounting Facility Screw Thread Series Designator:

Unc

#### Mounting Facility Type And Quantity:

2 threaded mounting studs

## **Features Provided:**

Hermetically sealed case

#### Capacitance Value Per Section:

0.200 microfarads single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 100.0 degrees celsius

## Thread Size:

0.112 inches

## Nonderated Continuous Voltage Rating And Type Per Section:

200.0 ac-rms single section and 400.0 dc single section

#### **Tolerance Range Per Section:**

-20.00/+20.00 percent single section

#### **Case Material:**

Metal

Insulation Resistance At Reference Temp:

250.0 megohm-microfarads

#### **Dissipation Factor At Reference Tempurature In Percent:**

1.000

## **Terminal Surface Treatment:**

Solder

# NSN 5910-00-822-9407

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



**Dielectric Material:** 

Paper

**Case Insulation Material:** 

Plastic

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0