NSN 5910-00-823-1083

Ceramic Dielectric Fixed Capacitor - Page 1 of 1



Body Style:
W/o mtg facilities, radial terminalsw/o mtg facilities, radial terminalsw/o mtg facilities, radial terminals
Reliability Indicator:
Not establishednot established
Terminal Length:
1.250 inches 1.250 inches 1.250 inches
Body Diameter:
0.594 inches
Body Length:
0.156 inches
Center To Center Distance Between Terminals Parallel To Diameter:
0.312 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
50.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
-220.0 single section
Nonderated Continuous Voltage Rating And Type Per Section:
500.0 dc single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-120.0/+120.0 single section
Tolerance Range Per Section:
-5.00/+5.00 percent single section
Case Material:
Ceramic
Terminal Surface Treatment:
Solder
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig:

A010b0