

View Online at <https://aerobasegroup.com/nsn/5910-00-823-1681>

Body Style:

W/o mtg facilities, radial terminalsw/o mtg facilities, radial terminalsw/o mtg facilities, radial terminals

Reliability Indicator:

Not establishednot establishednot established

Body Diameter:

0.360 inches

Body Length:

1.875 inches

Terminal Height From Body:

1.312 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Insulation Resistance At Maximum Operating Temp:

1000.0 megohms

Capacitance Value Per Section:

820.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-470.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

Tolerance Of Temperature Coefficient Per Section In Ppm Per Deg Celsius:

-60.0/+60.0 single section

Tolerance Range Per Section:

-1.00/+1.00 percent single section

Case Material:

Ceramic

Insulation Resistance At Reference Temp:

50000.0 megohms

Quality Factor At Reference Temp:

1000.0000

Terminal Surface Treatment:

Solder

Test Data Document:

81349-mil-c-20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0