NSN 5910-00-824-0086

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-824-0086

View Online at https://aerobasegroup.com/nsn/5910-00-824-0086
Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Not established
Terminal Length:
1.500 inches
Body Diameter:
0.219 inches
Body Length:
0.758 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Anode Type:
Etched foil
Impedance At Minimum Operating Tempurature In Ohms:
424.0
Electrical Polarization:
Polarized
Capacitance Value Per Section:
8.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Dc Leakage At Maximum Operating Temp:
6.0 milliamperes
Nonderated Continuous Voltage Rating And Type Per Section:
30.0 dc single section
Tolerance Range Per Section:
-15.00/+75.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Tantalum
Dc Leakage At Reference Temp:
2.000 microamperes
Terminal Surface Treatment:
Solder
Test Data Document:
81349-mil-c-3965 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
2 uninsulated wire lead

N/a

Shelf Life:

NSN 5910-00-824-0086

Electrolytic Fixed Capacitor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0