## NSN 5910-00-824-3977

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-824-3977

**Body Style:** Piston **Overall Length:** 2.237 inches **Terminal Length:** 0.500 inches **Body Length:** 2.050 inches **Overall Diameter:** 0.312 inches Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius: -50.0/+50.0 single section Center To Center Distance Between Terminals Parallel To Length: 2.000 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.234 inches **Terminal Diameter:** 0.030 inches **Center To Center Distance Between Mounting Facilities Parallel To Diameter:** 0.234 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 2.000 inches **Quality Factor At 25 Deg Celsius:** 250.0 **Inclosure Type:** Encapsulated **Adjustment Device Torque:** Between 1.000 inch-ounces and 10.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 1000.0 gigohms **Insulation Dc Resistance At Max Operating Temp:** 

100.0 gigohms

**Mounting Facility Type And Quantity:** 

4 terminal

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

Capacitance Range In Picofarads:

+1.0/+90.0 single section

**Nonderated Voltage Rating And Type:** 

1000.0 dc continuous single section

**Adjustment Device Drive Type And Quantity:** 

1 slotted screw

## NSN 5910-00-824-3977

Glass Dielectric Variable Capacitor - Page 2 of 2



Capacitance Drift In Picofarads:
0.08 single section
Terminal Type And Quantity:
4 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A096a0