

View Online at <https://aerobasegroup.com/nsn/5910-00-824-6880>

Thread Class:

2a

Body Style:

Piston

Bushing Diameter:

0.250 inches

Bushing Length:

0.250 inches

Body Length:

1.730 inches

Overall Diameter:

0.380 inches

Temperature Coefficient Of Capacitance Range In Ppm Per Deg Celsius:

-100.0/+100.0 single section

Quality Factor At 25 Deg Celsius:

500.0

Mounting Facility Screw Thread Series Designator:

Unef

Inclosure Type:

Encapsulated

Bushing Shape:

Round w/flat

Insulation Dc Resistance At 25 Deg Celsius:

1000.0 gigohms

Bushing Width:

0.225 inches

Mounting Facility Type And Quantity:

1 threaded bushing

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.250 inches

Capacitance Range In Picofarads:

+2.0/+29.0 single section

Nonderated Voltage Rating And Type:

1000.0 dc continuous single section

Capacitance Change In Percent At Operating Temperature From 25 Deg Celsius:

-1.00/+1.00 single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Capacitance Drift In Picofarads:

0.04 single section

Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A096a0