# NSN 5910-00-825-1842

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-825-1842

## **Body Style:**

W/o mtg facilities, terminal (s) on one surface

## **Reliability Indicator:**

Not established

## **Body Length:**

1.375 inches

#### Body Width:

1.312 inches

#### **Body Height:**

0.625 inches

## Schematic Diagram Designator:

No common or grounded electrode (s)

## Features Provided:

Hermetically sealed case

## Insulation Resistance At Maximum Operating Temp:

20.0 megohm-microfarads

## **Capacitance Value Per Section:**

0.100 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

1000.0 dc single section

## **Tolerance Range Per Section:**

-10.00 to 10.00 percent single section

#### **Case Material:**

Metal

#### Insulation Resistance At Reference Temp:

2000.0 megohm-microfarads

#### **Dissipation Factor At Reference Tempurature In Percent:**

1.0000

# **Terminal Surface Treatment:**

Solder

# Test Data Document:

81349-milc25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

# Unit Of Measure:

---

Demilitarization:

No

# NSN 5910-00-825-1842

Paper Dielectric Fixed Capacitor - Page 2 of 2

**Fiig:** A010b0

