

View Online at <https://aerobasegroup.com/nsn/5910-00-825-4636>

Body Style:

W/thd bushing mtg, terminal (s) on one end

Reliability Indicator:

Not established

Terminal Length:

0.590 inches

Body Diameter:

0.875 inches

Body Length:

1.250 inches

Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

Anode Type:

Solid

Impedance At Minimum Operating Tempurature In Ohms:

140.0

Electrical Polarization:

Polarized

Mounting Facility Screw Thread Series Designator:

Unf

Mounting Facility Type And Quantity:

1 threaded bushing

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

25.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.500 inches

Dc Leakage At Maximum Operating Temp:

128.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

180.0 dc single section

Tolerance Range Per Section:

-15.00/+75.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Tantalum

Equivalent Series Resistance At Reference Tempurature In Ohms:

5.30

Dc Leakage At Reference Temp:

44.000 microamperes

Test Data Document:

81349-mil-c-3965 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 tab, solder lug

Specification Data:

81349-mil-c-3965/1 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0