Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-825-7672

# **Body Style:**

W/o mtg facilities, terminal (s) on one surface

## **Reliability Indicator:**

Not established

# **Body Length:**

4.380 inches

#### Body Width:

1.380 inches

#### **Body Height:**

4.500 inches

### Center To Center Distance Between Terminals Parallel To Length:

3.250 inches

#### **Terminal Diameter:**

0.190 inches

#### **Terminal Height From Body:**

1.250 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

#### Features Provided:

Hermetically sealed case

## Capacitance Value Per Section:

0.300 microfarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

7500.0 dc single section

### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

### Case Material:

Metal

### Insulation Resistance At Reference Temp:

20000.0 megohm-microfarads

### **Dissipation Factor At Reference Tempurature In Percent:**

0.5000

### **Terminal Surface Treatment:**

Solder

### **Dielectric Material:**

Paper and plastic polyethylene terephthalate

# **Terminal Type And Quantity:**

2 standoff, threaded stud

#### Shelf Life:

N/a

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0