## NSN 5910-00-825-9383

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-825-9383

Body Style:
W/mtg tabs/flanges, terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
0.312 inches
Body Length:
2.000 inches
Body Width:
2.000 inches
Body Height:
1.750 inches
Unthreaded Mounting Hole Diameter:
0.190 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.380 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Internal Electrical Connection Type:
Extended foil
Mounting Facility Type And Quantity:
2 unthreaded mounting holes
Features Provided:
Hermetically sealed case
Insulation Resistance At Maximum Operating Temp:
10000.0 megohms
Capacitance Value Per Section:
1.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
-120.0 single section
Nonderated Continuous Voltage Rating And Type Per Section:
200.0 dc single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-30.0/+30.0 single section
Tolerance Range Per Section:
-0.10/+0.10 percent single section
Case Material:
Metal

100000.0 megohms

**Insulation Resistance At Reference Temp:** 

## NSN 5910-00-825-9383

Fiig: A010b0

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Dissipation Factor At Reference Tempurature In Percent:	
0.0250	
Dielectric Material:	
Plastic polystyrene	
Terminal Type And Quantity:	
2 tab, solder lug	
Shelf Life:	
N/a	
Unit Of Measure:	
<del>.</del>	
Demilitarization:	
No	