## NSN 5910-00-826-2719

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-826-2719

Body Style:	
W/o mtg facilities,	

axial terminals

**Reliability Indicator:** 

Not established

**Terminal Length:** 

1.625 inches

**Body Diameter:** 

0.463 inches

**Body Length:** 

0.463 inches

**Body Width:** 

0.463 inches

**Body Height:** 

0.463 inches

**Schematic Diagram Designator:** 

Electrod (s) grounded to case, w/gnd terminal

**Internal Electrical Connection Type:** 

Extended foil

**Features Provided:** 

Hermetically sealed case

**Insulation Resistance At Maximum Operating Temp:** 

10.0 megohm-microfarads

**Capacitance Value Per Section:** 

0.100 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

**Tolerance Range Per Section:** 

-10.00 to 10.00 percent single section

**Case Material:** 

Metal

**Insulation Resistance At Reference Temp:** 

18000.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:** 

1.0000

**Terminal Surface Treatment:** 

Solder

**Test Data Document:** 

81349-mil-c-25/1k specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-00-826-2719

Paper Dielectric Fixed Capacitor - Page 2 of 2



She	lf	Life:	
Oile	••	LIIV.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0