## NSN 5910-00-826-2823

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-826-2823

	Stv	

W/o mtg facilities terminal (s) on one surfacew/o mtg facilities terminal(s) on one surface

**Reliability Indicator:** 

Not establishednot established

**Terminal Length:** 

1.250 inches 1.250 inches

**Body Length:** 

0.420 inches

Body Width:

0.420 inches

**Body Height:** 

0.120 inches

Center To Center Distance Between Terminals Parallel To Length:

0.200 inches

**Terminal Diameter:** 

0.025 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Insulation Resistance At Maximum Operating Temp:** 

1000.0 megohms

**Capacitance Value Per Section:** 

18000.000 picofarads single section

Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-40.0/+10.0 without voltage applied single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 150.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+10.00 percent single section

**Case Material:** 

Plastic or glass

**Insulation Resistance At Reference Temp:** 

10000.0 megohms

**Power Factor At Reference Tempurature In Percent:** 

2.5000

**Terminal Surface Treatment:** 

Solder

**Test Data Document:** 

97942-576r461h32 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-00-826-2823

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0