

View Online at https://aerobasegroup.com/nsn/5910-00-826-5811

Body Style:	
Button type, w/mtg tabs	
Reliability Indicator:	
Not established	
Body Diameter:	
0.450 inches	
Body Length:	
0.085 inches	
Schematic Diagram Desigr	ator:
Electrod (s) grounded to cas	e
Insulation Resistance At M	aximum Operating Temp:
15000.0 megohms	
Capacitance Value Per Sec	tion:
10.000 picofarads single sec	ion
Nonderated Operating Ten	p:
Between -55.0 degrees celsi	us and 85.0 degrees celsius
Nonderated Continuous Vo	Itage Rating And Type Per Section:
500.0 dc single section	
Tempurature Coefficient O	Capacitance Range Per Section In Ppm Per Deg Celsius:
-100.0 to 100.0 single sectio	1
Tolerance Range Per Secti	on:
-10.00 to 10.00 percent singl	e section
Case Material:	
Metal	
Insulation Resistance At R	eference Temp:
50000.0 megohms	
Dissipation Factor At Refe	ence Tempurature In Percent:
0.0060	
Terminal Surface Treatmer	t:
Silver	
Test Data Document:	
81349-mil-c-10950+1 specifi	cation (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercia	l catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performa	nce requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantit	y:
1 unthreaded hole	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A010b0	