

View Online at <https://aerobasegroup.com/nsn/5910-00-827-9843>

**Body Style:**

W/thd mtg bushing, terminals on opposite ends/w/thd mtg bushing, terminals on opposite ends/w/thd mtg bushing, terminals on opposite ends/w/thd mtg bushing, terminals on opposite ends

**Reliability Indicator:**

Not established/not established/not established/not established

**Width Across Flats:**

0.312 inches 0.312 inches 0.312 inches 0.312 inches

**Terminal Length:**

0.188 inches 0.188 inches 0.188 inches

**Body Length:**

0.468 inches 0.468 inches

**Terminal Diameter:**

0.051 inches 0.051 inches

**Schematic Diagram Designator:**

Feedthrough/feedthrough

**Mounting Facility Screw Thread Series Designator:**

Unfunf

**Mounting Facility Type And Quantity:**

1 threaded bushing/1 threaded bushing

**Capacitance Value Per Section:**

1500.000 microfarads single section/1500.000 microfarads single section

**Voltage Temperature Limits Per Section In Percent Capacitance Change:**

-82.0/+22.0 without voltage applied single section/-82.0/+22.0 without voltage applied single section

**Nonrated Operating Temp:**

Between -55.0 degrees celsius and -55.0 degrees celsius and 95.0 degrees celsius/95.0 degrees celsius

**Thread Size:**

0.250 inches/0.250 inches

**Nonrated Continuous Voltage Rating And Type Per Section:**

500.0 dc single section/500.0 dc single section

**Tolerance Range Per Section:**

-20.00/+20.00 percent single section/-20.00/+20.00 percent single section

**Case Material:**

Metal/metal

**Power Factor At Reference Temperature In Percent:**

2.0000/2.0000

**Precious Material And Location:**

Bushing silver/bushing silver

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0