NSN 5910-00-828-2061

Air Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-828-2061

Body Style:

Plate-meshing

Overall Length:

Between 0.563 inches and 0.635 inches

Terminal Length:

Between 0.125 inches and 0.187 inches

Overall Height:

Between 0.441 inches and 0.465 inches

Overall Width:

Between 0.421 inches and 0.445 inches

Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius:

45.0 single section

Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:

-15.0/+15.0 single section

Center To Center Distance Between Terminals Parallel To Length:

Between 0.369 inches and 0.431 inches

Unthreaded Mounting Hole Diameter:

Between 0.067 inches and 0.075 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 0.291 inches and 0.299 inches

Quality Factor At 25 Deg Celsius:

2000.0

Fragility Factor:

Moderately rugged

Terminal Width:

0.047 inches

Terminal Thickness:

0.016 inches

End Application:

2spruance class dd (963); virginia class cgn (41); forrestal class cv; arleigh burke class ddg; landing craft air cushion (lcac); kidd class ddg; sturgeon class ssn (637); ticonderoga class cg (47); los angeles class ssn (688); nimitz class cv

Inclosure Type:

Uninclosed

Plate Quantity:

12

Tuning Characteristic:

Straight line capacity single section

Adjustment Device Rotation:

180.0 degrees clockwise

Insulation Dc Resistance At 25 Deg Celsius:

100000.0 megohms

Plate Air Gap:

0.010 inches

NSN 5910-00-828-2061

Air Dielectric Variable Capacitor - Page 2 of 2



Mounting Facility Type And Quantity:
2 unthreaded hole
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Criticality Code Justification:
Feat
Capacitance Range In Picofarads:
+1.7/+14.1 single section
Nonderated Voltage Rating And Type:
650.0 ac peak single section
Adjustment Device Drive Type And Quantity:
1 slotted screw
Capacitance Drift In Picofarads:
0.04 single section
Special Features:
Weapon system essential
Material:
Steatite base
Precious Material And Location:
Metal surfaces silver
Precious Material:
Silver
Terminal Type And Quantity:
2 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A096a0