Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



NSN 5910-00-828-7456 View Online at https://aerobasegroup.com/nsn/5910-00-828-7456 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 2.000 inches **Body Length:** Between 1.980 inches and 2.000 inches **Body Width:** Between 0.980 inches and 1.000 inches **Body Height:** Between 0.700 inches and 0.800 inches Center To Center Distance Between Terminals Parallel To Length: Between 1.750 inches and 1.870 inches

Terminal Diameter:

0.032 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Capacitance Value Per Section:

8.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

500.0 megohm-microfarads

Dissipation Factor At Reference Tempurature In Percent:

1.000

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5910-00-828-7456

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig:

A010b0