## NSN 5910-00-828-8025

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-828-8025

<b>Body</b>	Sty	٠ما
DUUV	OLV.	ıe.

W/o mtg facilities, radial terminalsw/o mtg facilities, radial terminals

**Reliability Indicator:** 

Not establishednot established

**Terminal Length:** 

1.250 inches 1.250 inches

**Body Diameter:** 

0.200 inches

**Body Length:** 

0.400 inches

**Center To Center Distance Between Terminals Parallel To Length:** 

Between 0.190 inches and 0.310 inches

**Terminal Diameter:** 

0.025 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Capacitance Value Per Section:** 

6.000 picofarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

**Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** 

-60.0/+60.0 single section

**Tolerance Range Per Section:** 

-0.50/+0.50 picofarads single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

10000.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:** 

2.000

**Terminal Surface Treatment:** 

Solder

**Terminal Type And Quantity:** 

2 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5910-00-828-8025

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0