## NSN 5910-00-828-9534

Ceramic Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-828-9534 **Body Style:** Rotary **Terminal Length:** 0.130 inches **Overall Height:** 0.315 inches **Overall Diameter:** 0.276 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 100.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -250.0/+250.0 single section **Center To Center Distance Between Terminals Parallel To Diameter:** 0.315 inches **Quality Factor At 25 Deg Celsius:** 300.0 **Fragility Factor:** Moderately rugged **Terminal Width:** 0.079 inches **Terminal Thickness:** 0.020 inches **Inclosure Type:** Uninclosed **Adjustment Device Torque:** Between 0.500 inch-ounces and 5.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 10.0 gigohms **Mounting Facility Type And Quantity:** 3 terminal **Nonderated Operating Temp:** Between -20.0 degrees celsius and 70.0 degrees celsius Capacitance Range In Picofarads: +1.7/+10.0 single section **Nonderated Voltage Rating And Type:** 500.0 dc continuous single section **Adjustment Device Drive Type And Quantity:** 1 slotted screw Material: Ceramic inclosure **Terminal Type And Quantity:** 

3 printed circuit

## NSN 5910-00-828-9534

Ceramic Dielectric Variable Capacitor - Page 2 of 2



N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A096a0