## NSN 5910-00-829-3438

W/thd bushing mtg, terminal (s) on one end

**Body Style:** 

Reliability Indicator:

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-829-3438

Not established
Terminal Length:
1.625 inches
Body Diameter:
0.670 inches
Body Length:
1.563 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
Electrod (s) grounded to case
Mounting Facility Screw Thread Series Designator:
Unf
Mounting Facility Type And Quantity:
1 threaded bushing
Insulation Resistance At Maximum Operating Temp:
5.0 megohm-microfarads
Capacitance Value Per Section:
0.680 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Thread Size:
0.312 inches
Nonderated Continuous Voltage Rating And Type Per Section:
400.0 dc single section
Tolerance Range Per Section:
-20.00/+20.00 percent single section
Case Material:
Metal
Insulation Resistance At Reference Temp:
2000.0 megohm-microfarads
Power Factor At Reference Tempurature In Percent:
1.5000
Terminal Surface Treatment:
Solder
Terminal Type And Quantity:
1 uninsulated wire lead
Shelf Life:
N/a

## NSN 5910-00-829-3438

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A010b0