NSN 5910-00-832-5900

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-832-5900

3
Body Style:
W/mtg tabs/flanges terminal (s) on one surface
Reliability Indicator:
Not established
Body Length:
2.000 inches
Body Width:
2.000 inches
Body Height:
3.000 inches
Unthreaded Mounting Hole Diameter:
0.156 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.375 inches
Schematic Diagram Designator:
One terminal common to each section
Mounting Facility Type And Quantity:
2 unthreaded mounting holes
Section Quantity:
2
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
30.000 microfarads all sections
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
200.0 dc all sections
Tolerance Range Per Section:
-5.00/+5.00 percent all sections
Case Material:
Metal
Insulation Resistance At Reference Temp:
12000.0 megohm-microfarads
Dissipation Factor At Reference Tempurature In Percent:
1.000
Terminal Surface Treatment:
Solder
Test Data Document:
10001-738829 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.

excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

3 tab, solder lug

NSN 5910-00-832-5900

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Shelf	Life:
N/a	

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0