NSN 5910-00-832-9206

Not establishednot established

Body Style:

Reliability Indicator:

Terminal Length:

1.250 inches 1.250 inches

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-832-9206

W/o mtg facilities, radial terminalsw/o mtg facilities, radial terminalsw/o mtg facilities, radial terminals

Body Diameter:
0.625 inches
Body Length:
0.156 inches
Center To Center Distance Between Terminals Parallel To Diameter:
0.375 inches
Terminal Diameter:
0.032 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
0.010 microfarads single section
Voltage Tempurature Limits Per Section In Percent Capacitance Change:
-56.0/+22.0 with 500 volts applied single section
Nonderated Operating Temp:
Between 10.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
1000.0 dc single section
Tolerance Range Per Section:
-20.00/+20.00 percent single section
Coop Metaviol.
Case Material:
Plastic
Plastic
Plastic Insulation Resistance At Reference Temp:
Plastic Insulation Resistance At Reference Temp: 10000.0 megohms
Plastic Insulation Resistance At Reference Temp: 10000.0 megohms Dissipation Factor At Reference Tempurature In Percent:
Plastic Insulation Resistance At Reference Temp: 10000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 2.5000
Plastic Insulation Resistance At Reference Temp: 10000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 2.5000 Terminal Surface Treatment:
Plastic Insulation Resistance At Reference Temp: 10000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 2.5000 Terminal Surface Treatment: Solder
Plastic Insulation Resistance At Reference Temp: 10000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 2.5000 Terminal Surface Treatment: Solder Terminal Type And Quantity:
Plastic Insulation Resistance At Reference Temp: 10000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 2.5000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead
Plastic Insulation Resistance At Reference Temp: 10000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 2.5000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life:
Plastic Insulation Resistance At Reference Temp: 10000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 2.5000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a
Plastic Insulation Resistance At Reference Temp: 10000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 2.5000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a

NSN 5910-00-832-9206

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0