NSN 5910-00-832-9750

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-832-9750

| Body Style: |
|-----------------------------------------------------------------------------------------------------------|
| W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals |
| Reliability Indicator: |
| Not establishednot established |
| Terminal Length: |
| Between 1.250 inches and 1.750 inches |
| Body Diameter: |
| 0.115 inches |
| Body Length: |
| 0.250 inches |
| Terminal Diameter: |
| 0.028 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Insulation Resistance At Maximum Operating Temp: |
| 5000.0 megohms |
| Capacitance Value Per Section: |
| 1.500 picofarads single section |
| Voltage Tempurature Limits Per Section In Percent Capacitance Change: |
| -3.5/+3.5 without voltage applied single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 500.0 dc single section |
| Tolerance Range Per Section: |
| -5.00/+5.00 percent single section |
| Case Material: |
| Plastic |
| Insulation Resistance At Reference Temp: |
| 50000.0 megohms |
| Quality Factor At Reference Temp: |
| 100.000 |
| Terminal Surface Treatment: |
| Solder |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

No

Demilitarization:

NSN 5910-00-832-9750

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0