NSN 5910-00-834-6176

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-834-6176

view Orimine at https://derobasegroup.com/nsi//0910-00-004-0170
Body Style:
W/o mtg facilities, terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
0.312 inches
Body Length:
1.367 inches
Body Width:
0.782 inches
Body Height:
2.500 inches
Center To Center Distance Between Terminals Parallel To Length:
0.640 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Anode Type:
Solid
Impedance At Minimum Operating Tempurature In Ohms:
4.0
Electrical Polarization:
Polarized
Capacitance Value Per Section:
1800.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Dc Leakage At Maximum Operating Temp:
250.0 microamperes
Nonderated Continuous Voltage Rating And Type Per Section:
30.0 dc single section
Tolerance Range Per Section:
-20.00/+20.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Tantalum
Dissipation Factor At Reference Tempurature In Percent:
30.0000
Dc Leakage At Reference Temp:
25.000 microamperes

2 tab, solder lug

Terminal Type And Quantity:

NSN 5910-00-834-6176

Electrolytic Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0