NSN 5910-00-834-7017

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-834-7017
Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Not established
Terminal Length:
Between 1.625 inches and 2.625 inches
Body Diameter:
Between 0.169 inches and 0.189 inches
Body Length:
Between 0.594 inches and 0.656 inches
Terminal Diameter:
0.020 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Insulation Resistance At Maximum Operating Temp:
10.0 megohm-microfarads
Capacitance Value Per Section:
0.010 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
200.0 dc single section
Tolerance Range Per Section:
-5.00/+5.00 percent single section
Case Material:
Metal
Insulation Resistance At Reference Temp:
50000.0 megohm-microfarads
Dissipation Factor At Reference Tempurature In Percent:
1.500
Terminal Surface Treatment:
Solder
Dielectric Material:
Plastic polyester
Case Insulation Material:
Plastic
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
Shell Life.

--

Unit Of Measure:

NSN 5910-00-834-7017

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



_		••	• -				
1	em		ゖっ	riz	2 †1	n	
_			ıιa	114	au	VII	١.

No

Fiig:

A010b0