NSN 5910-00-835-2713

A010b0

Plastic Dielectric Fixed Capacitor - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5910-00-835-2713 |
|--|
| Body Style: |
| W/o mtg facilities, axial terminals |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| Between 1.625 inches and 2.625 inches |
| Body Diameter: |
| 0.172 inches |
| Body Length: |
| 0.688 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Insulation Resistance At Maximum Operating Temp: |
| 300.0 megohms |
| Capacitance Value Per Section: |
| 12000.000 picofarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 125.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 50.0 dc single section |
| Tolerance Range Per Section: |
| -10.00/+10.00 percent single section |
| Case Material: |
| Plastic |
| Insulation Resistance At Reference Temp: |
| 100000.0 megohms |
| Terminal Surface Treatment: |
| Solder |
| Test Data Document: |
| 81349-mil-c-27287/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| File: |