NSN 5910-00-835-2716

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-835-2716
Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Not established
Terminal Length:
2.125 inches
Body Diameter:
0.188 inches
Body Length:
0.688 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Internal Electrical Connection Type:
Extended foil
Insulation Resistance At Maximum Operating Temp:
300.0 megohms
Capacitance Value Per Section:
18000.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc single section
Tolerance Range Per Section:
-5.00/+5.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
100000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
1.0000
Terminal Surface Treatment:
Solder
Dielectric Material:
Plastic polyethylene terephthalate
Test Data Document:
81349-mil-c-27287 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a

--

Unit Of Measure:

NSN 5910-00-835-2716

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0