## NSN 5910-00-835-2766

Quartz Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-835-2766 **Thread Class:** 2a **Body Style:** Piston **Overall Length:** Between 1.594 inches and 1.656 inches **Terminal Length:** 1.500 inches **Bushing Diameter:** 0.190 inches **Bushing Length:** 0.250 inches **Body Length:** Between 1.344 inches and 1.406 inches **Overall Diameter:** 0.375 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -100.0/+100.0 single section **Terminal Diameter:** 0.032 inches **Quality Factor At 25 Deg Celsius:** 2000.0 **Fragility Factor:** Moderately rugged **Mounting Facility Screw Thread Series Designator:** Unf **Inclosure Type: Encased Adjustment Device Torque:** Between 1.000 inch-ounces and 10.000 inch-ounces **Bushing Shape:** Round Insulation Dc Resistance At 25 Deg Celsius: 1000000.0 megohms **Mounting Facility Type And Quantity:** 1 threaded bushing **Nonderated Operating Temp:** Between -55.0 degrees celsius and 200.0 degrees celsius

**Thread Size:** 

0.190 inches

## NSN 5910-00-835-2766

Quartz Dielectric Variable Capacitor - Page 2 of 2



| Capacitance Range In Picofarads:           |
|--|
| +0.5/+5.0 single section                   |
| Nonderated Voltage Rating And Type:        |
| 2500.0 dc continuous single section        |
| Adjustment Device Drive Type And Quantity: |
| 1 slotted screw                            |
| Capacitance Drift In Picofarads:           |
| 0.04 single section                        |
| Material:                                  |
| Quartz capacitive electrode                |
| Terminal Type And Quantity:                |
| 1 wire lead                                |
| Shelf Life:                                |
| N/a  |
| Unit Of Measure:                           |
|  |
| Demilitarization:                          |
| No   |

**Fiig:** A096a0