

View Online at <https://aerobasegroup.com/nsn/5910-00-835-2766>

Thread Class:

2a

Body Style:

Piston

Overall Length:

Between 1.594 inches and 1.656 inches

Terminal Length:

1.500 inches

Bushing Diameter:

0.190 inches

Bushing Length:

0.250 inches

Body Length:

Between 1.344 inches and 1.406 inches

Overall Diameter:

0.375 inches

Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:

0.0 single section

Tolerance Of Temperature Coefficient In Ppm Per Deg Celsius:

-100.0/+100.0 single section

Terminal Diameter:

0.032 inches

Quality Factor At 25 Deg Celsius:

2000.0

Fragility Factor:

Moderately rugged

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Encased

Adjustment Device Torque:

Between 1.000 inch-ounces and 10.000 inch-ounces

Bushing Shape:

Round

Insulation Dc Resistance At 25 Deg Celsius:

1000000.0 megohms

Mounting Facility Type And Quantity:

1 threaded bushing

Nonderated Operating Temp:

Between -55.0 degrees celsius and 200.0 degrees celsius

Thread Size:

0.190 inches

Capacitance Range In Picofarads:

+0.5/+5.0 single section

Nonderated Voltage Rating And Type:

2500.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Capacitance Drift In Picofarads:

0.04 single section

Material:

Quartz capacitive electrode

Terminal Type And Quantity:

1 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0