

View Online at https://aerobasegroup.com/nsn/5910-00-835-2953

## **Body Style:**

W/o mtg facilities, axial terminals

# **Reliability Indicator:**

Not established

# **Terminal Length:**

2.125 inches

# **Body Diameter:**

0.329 inches

### **Body Length:**

1.062 inches

## Schematic Diagram Designator:

No common or grounded electrode (s)

## Internal Electrical Connection Type:

Extended foil

## Insulation Resistance At Maximum Operating Temp:

20.0 megohm-microfarads

### **Capacitance Value Per Section:**

0.100 microfarads single section

# Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

# **Tolerance Range Per Section:**

-5.00/+5.00 percent single section

### **Case Material:**

Plastic

### Insulation Resistance At Reference Temp:

100000.0 megohms

### **Dissipation Factor At Reference Tempurature In Percent:**

1.0000

# **Terminal Surface Treatment:**

Solder

# **Dielectric Material:**

Plastic polyethylene terephthalate

# **Test Data Document:**

81349-mil-c-27287 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Terminal Type And Quantity:**

2 uninsulated wire lead

#### Shelf Life:

N/a

Unit Of Measure:

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0