NSN 5910-00-835-3509

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-835-3509

Body Style:	
W/o mtg facilities, axial terminals	
Reliability Indicator:	
Not established	
Terminal Length:	
Between 1.625 inches and 2.625 inches	
Body Diameter:	
0.548 inches	
Body Length:	
1.562 inches	
Terminal Diameter:	
0.032 inches	
Schematic Diagram Designator:	
No common or grounded electrode (s)	
Internal Electrical Connection Type:	
Extended foil	
Insulation Resistance At Maximum Operating Temp:	
20.0 megohm-microfarads	
Capacitance Value Per Section:	
1.000 microfarads single section	
Nonderated Operating Temp:	
Between -55.0 degrees celsius and 125.0 degrees celsius	
Nonderated Continuous Voltage Rating And Type Per Section:	
50.0 dc single section	
Tolerance Range Per Section:	
-5.00/+5.00 percent single section	
Case Material:	
Plastic	
Insulation Resistance At Reference Temp:	
25000.0 megohm-microfarads	
Dissipation Factor At Reference Tempurature In Percent:	
1.000	
Terminal Surface Treatment:	
Solder	
Dielectric Material:	
Plastic polyethylene	
Test Data Document:	
81349-mil-c-27287 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification	
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Terminal Type And Quantity:	
2 uninsulated wire lead	

Specification Data: 81349-mil-c-27287/1 government specification

NSN 5910-00-835-3509

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Shelf	Life:
N/a	

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0