

View Online at <https://aerobasegroup.com/nsn/5910-00-836-6258>

**Body Style:**

W/o mtg facilities, terminal (s) on one end

**Reliability Indicator:**

Not established

**Body Diameter:**

1.375 inches

**Body Length:**

2.125 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Plain foil

**Electrical Polarization:**

Polarized

**End Application:**

Forrestal class cv; wasp class lhd; virginia class cgn (41); whidbey island class lsd; ticonderoga class cg (47); oliver perry class ffg; tarawa class lha; general purpose electronic test equipment gpete; iwo jima class lph

**Capacitance Value Per Section:**

1300.000 microfarads single section

**Nonderated Operating Temp:**

Between -20.0 degrees celsius and 85.0 degrees celsius

**Dc Leakage At Maximum Operating Temp:**

15.0 milliamperes

**Nonderated Continuous Voltage Rating And Type Per Section:**

50.0 dc single section

**Criticality Code Justification:**

Feat

**Tolerance Range Per Section:**

-10.00/+75.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Aluminum

**Equivalent Series Resistance At Reference Temperature In Ohms:**

0.40

**Dc Leakage At Reference Temp:**

6.000 milliamperes

**Case Insulation Material:**

Plastic

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

2 threaded hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0