

View Online at <https://aerobasegroup.com/nsn/5910-00-836-6258>

Body Style:

W/o mtg facilities, terminal (s) on one end

Reliability Indicator:

Not established

Body Diameter:

1.375 inches

Body Length:

2.125 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Plain foil

Electrical Polarization:

Polarized

End Application:

Forrestal class cv; wasp class lhd; virginia class cgn (41); whidbey island class lsd; ticonderoga class cg (47); oliver perry class ffg; tarawa class lha; general purpose electronic test equipment gpete; iwo jima class lph

Capacitance Value Per Section:

1300.000 microfarads single section

Nonderated Operating Temp:

Between -20.0 degrees celsius and 85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

15.0 milliamperes

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-10.00/+75.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Temperature In Ohms:

0.40

Dc Leakage At Reference Temp:

6.000 milliamperes

Case Insulation Material:

Plastic

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0